

DATASHEET REMOTE MONITORING WLan-WW

Fox ESS WLan-WW





Easy Installation

plug and play installation.



Strong Signal Strong LAN signal for maximum range.



Suitable for outdoor installation.



Connect to the Fox ESS Cloud.

The WLan-WW is an intelligent LAN enabled device allowing you to monitor the status and performance of your Fox ESS PV system via the Fox ESS Cloud remote monitoring platform. The WLan-WW is ideal is situations where there is no reliable GPRS or 4G connection available.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.

- Stable lan communication
- IP65 protection class
- Clean and compact design
- User-friendly monitoring app
- Plug and play installation
- Monitor your system from anywhere
- 24/7 monitoring





Fox ESS SMART LAN WLan-WW

SPECIFICATIONS	
Model Name	WLan-WW
Input Voltage [V]	DC 7 ~ 12
Power Consultation [W]	Тур.3
Frequency Range [GHz]	2.4 ~ 2.472
Wireless Standards [b/g/n]	802.11
Antenna Gain [dB]	3
Security	WEP/WPA-PSK/WPA2-PSK
Protocol	TCP/UDP/HTTP/MQTT/SSL
Baud Rate	9600/8/n/1
Transmitting Power [dBm]	19.5@11b, 14@11g, 13@11n
User Configuration Interface	DHCP/Static IP/Firmware Upload
Physical Interface	USB, RJ45
Antenna	PCB antenna internal
Red LED	Detail in quickly install manual
Green LED	Detail in quickly install manual
Dimension (W*H*D) [mm]	130.0*48.0*27.0
Weight [g]	62
Installation Type	Plug-in
Operating Temperature [°C]	-25 ~ +60
Storage Temperature [°C]	-25 ~ +60
Operating Humidity [%]	≤95, Non-condensing
IP Level	IP65
CE-ROHS	2011/65/EU and 2015/863/EU