

## Enphase Envoy-S Standard

The **Enphase Envoy-S Standard™** communications gateway delivers solar production data to Enphase Enlighten™ monitoring and analysis software for comprehensive, remote maintenance and management of the Enphase System.

With multiple powering and connection options, Envoy-S Standard allows for greatest installation flexibility.



### Smart

- Enables web-based monitoring and control
- Bidirectional communications for remote upgrade

### Simple

- Easy system configuration using Enphase Installer Toolkit™ mobile app
- Flexible networking with Wi-Fi, Ethernet, or mobile

### Reliable

- Designed for installation indoors or in an outdoor enclosure
- Five-year warranty

# Enphase Envoy-S Standard

## MODEL NUMBERS

|  |  |
|--|--|
| Envoy-S Standard<br>ENV-S-WB-230-F, G, and I | Enphase Envoy-S communications gateway with basic PV production monitoring (+/- 5%). |
|--|--|

## ACCESSORIES (Order Separately)

|   |  |
|---|--|
| Enphase Mobile Connect™<br>CELLMODEM-02 | Plug and play industrial grade mobile modem with five-year data plan for systems up to 60 microinverters. (Available where there is adequate mobile service in the installation area.) |
|---|--|

## POWER REQUIREMENTS

|                |  |
|----------------|--|
| Cord connected | 230 VAC, 50 Hz. Max 20 A over current protection required.                 |
| Hardwired      | 230 VAC or 400Y/230 VAC, 50 Hz. Max 20 A over current protection required. |

## CAPACITY

|                                 |           |
|---------------------------------|-----------|
| Number of microinverters polled | Up to 600 |
|---------------------------------|-----------|

## MECHANICAL DATA

|                           |  |
|---------------------------|--|
| Dimensions (WxHxD)        | 213 x 126 x 45 mm  |
| Weight                    | 0.5 kg   |
| Ambient temperature range | -40° to 65° C<br>-40° to 46° C if installed in an enclosure                              |
| Environmental rating      | IP30. If installed outdoors, install the Envoy-S in an IP54-rated (or better) enclosure. |
| Altitude                  | To 2000 meters   |
| USB ports                 | Two USB 2.0 ports, auto-sensing, auto-negotiation  |

## INTERNET CONNECTION OPTIONS

|                  |   |
|------------------|---|
| Integrated Wi-Fi | 802.11b/g/n (2.4 GHz, 5 GHz)  |
| Ethernet         | Optional, 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included) |
| Mobile           | Optional, CELLMODEM-02 (not included)                               |

## COMPLIANCE

|            |  |
|------------|--|
| Compliance | IEC/EN 61010-1:2010,<br>EN50065-1, EN61000-4-5, EN61000-6-1, EN61000-6-2 |
|------------|--|

To learn more about Enphase offerings, visit [enphase.com/uk](http://enphase.com/uk)

© 2016 Enphase Energy. All rights reserved. All trademarks or brands in this document are registered by their respective owner.  
2016/05/13

